

**COMMUNICATION NETWORK WITH A COLLECTION GATEWAY AND
METHOD FOR PROVIDING SURVEILLANCE SERVICES**

Cross-reference to Related Application

5 This application is based on prior U.S. Patent Application No. 60/195,723, filed April 7, 2000, and priority thereto is hereby claimed.

Field of the Invention

10 The present invention relates generally to communication networks, and more particularly, to a communication network, an apparatus and a method for providing surveillance services.

15 Background of the Invention

Under certain circumstances, and with appropriate authorization, law enforcement agencies (LEA) are permitted to legally intercept and monitor communications between individuals that may be targets of an investigation. A
20 common technique, known as wiretapping, involves intercepting telephonic communications between individuals by "tapping" into the communication.

Plain old telephone systems (POTS) and early wireless communication systems incorporating, Class 4 or Class 5
25 exchanges, a Mobile Switching Center (MSC) and the like, employ circuit switching techniques to connect a calling party to a called party via a communication network. The call is completed upon successfully establishing the circuit between the parties, and the circuit becomes a dedicated
30 link between the parties for carrying on the telephonic communications. All voice communication between the parties is then carried on this circuit.

To provide surveillance, or wiretapping, in such circuit switched systems required only determining and "tapping" the circuit at an appropriate location along the circuit. A circuit is dedicated to the call, and because
5 all of the communications are carried on this circuit, the LEA can be assured of intercepting the entire communication, including in-band and out-of-band call signaling, between the individuals under surveillance from this one tap.

Evolution of communications technology will render
10 obsolete the circuit switched network for both voice and data communication networks. In fact, circuit switched networks are being replaced by packet-based communication networks. In packet-based networks, the information carried by the network, for example data or encoded voice, is
15 organized into packets, and the network carries these packets from the sending party to the receiving party. Within the network there is no single path or "circuit" that carries the packets from the sending party to the receiving party. Instead, the network may be considered a fabric of
20 links, switches and routers that carry packets in an efficient manner. Packets associated with the communications of a first party with a second party may travel on any number of paths. This arrangement of the packet based communication network permits more efficient
25 utilization of communication resources, and hence, permits the communication network to carry more information, with greater stability. Thus, the packet based communication network can service a greater number of users communicating greater amounts of information, i.e., both voice and data.

30 The Communications Assistance for Law Enforcement Act of 1994 (CALEA) requires that all US based wireline, cellular and broadband personal communication services (PCS)

carriers provide the capability of legal, undetectable, bearer and call signaling intercept to law enforcement agencies for any subscriber utilizing their network. CALEA implementation, which is governed by Federal Communication Commission (FCC) regulations, must be completed by June 30, 2000 for non-packet-based networks and by September 30, 2001 for packet-based networks. While the FCC has specified the required functionality, it has not specified or recommended architecture for achieving compliance with its regulations.

As described above in connection with circuit-based, or non-packet-based networks, providing surveillance capability generally requires only determining the particular circuit established for a communication, and intercepting both the bearer and call signaling information carried on that circuit. However, in packet-based networks no single circuit or path carries the data packets which include the bearer and call signaling information. To ensure complete surveillance, it is necessary to ensure that all packets associated with a communication are identified regardless of the path assigned to any particular packet.

Additionally, the FCC regulations specify certain functional requirements beyond bearer and call signaling intercept that must be met for compliance with the CALEA legislation. The regulations are completely set forth in the interim standard J-STD-025, available from the Federal Communication Commission, 445 12th Street S.W., Washington, D.C., 20554. Among these requirements are a capability to provide: content of subject-initiated conference calls, party hold, join, drop on conference call, in-band and out-of-band signaling, timing information, dialed digit extraction, and no interruption of call performance, billing, etc. as a result of CALEA implementation.

Thus, there is a need for a communication network and method that includes surveillance capability and which utilizes packet switched data techniques for providing communication services.

5

Brief Description of the Drawings

FIG. 1 is a block diagram illustration of a communication network in accordance with a preferred embodiment of the present invention.

10 FIG. 2 is a call flow diagram illustrating a method of surveillance in a packet data network in accordance with a preferred embodiment of the present invention.

FIG. 3 is a block diagram illustration of a communication network in accordance with another preferred
15 embodiment of the present invention.

FIG. 4 is a call flow diagram illustrating a method of surveillance in a packet data network such as illustrated in FIG. 3.

FIG. 5 is a block diagram illustration of a
20 communication network in accordance with yet another preferred embodiment of the present invention.

FIG. 6 is a block diagram illustration of a communication network in accordance with still another preferred embodiment of the present invention.

25 FIGS. 7-10 are call flow diagrams illustrating a method of providing surveillance in a packet data network such as illustrated in FIG. 6.

FIG. 11 is a block diagram illustration of a communication network in accordance with yet another
30 preferred embodiment of the invention.

Detailed Description of the Preferred Embodiments

In accordance with the preferred embodiments of the invention, a communication network utilized for providing communications between a first party and a second party includes a surveillance server within a core network to provide communication surveillance capability. The core network may be a packet data network, and the surveillance server is operable responsive to trigger information to establish communications surveillance. Communication surveillance may be established by creating duplicate bearer packets of those data packets carrying the communicated data between the parties, creating duplicate control packets of those data packets carrying in-band or out-of-band call control information between the parties and within the packet data network, and/or various combinations thereof. The duplicate bearer packets and the duplicate control packets are routed to appropriate authorized law enforcement agencies for providing surveillance. Since these bearer packets are digitally encoded, the law enforcement agency will require encoding information on the bearer stream so that the packets can be decoded. Therefore, bearer packet encoding information must be sent to the law enforcement agency prior to initiating the duplication of bearer packets.

Consistent with the preferred embodiments of the present invention, the surveillance server (e.g., feature server) may be disposed within a packet data network and apart from external networks accessing the core network, the surveillance server may be associated with one or more network access servers and/or the surveillance server may be associated with one or more of the external accessing networks.

In accordance with preferred methods of providing surveillance within a packet data network, a surveillance server is provided either associated with or apart from the core network and in communication with the core network.

5 The surveillance server identifies a trigger event, and responsive to the trigger event, causes the creation of duplicate bearer packets and/or duplicate control packets, and routes the duplicate packets to appropriate authorized law enforcement agencies.

10 With reference to FIG. 1, a communication core network 10 is coupled for communication with a radio access network 12, a public switch telephone network (PSTN) 14, a packet data network and/or the Internet 16, and a Signaling System 7 (SS7) network 18. It should be appreciated that the core
15 network 10 may be coupled, via gateways (e.g., an SS7 Gateway 28, a packet gateway 30 or a PSTN gateway 32), for communication to additional networks of operating under virtually any protocol.

Within the core network 10 are a number of elements
20 including a services client 20, a PSTN/MGC 22, a relay client 24, and a CALEA feature server 26. The relay client 24 provides an interface between the core network 10 and the radio access network 12 for providing wireless communication services to subscribers, not shown, utilizing the radio
25 access network 12 for wireless voice and data communications. Within the radio access network 12, a bearer client 13 provides the communication services to the subscribers, and is interfaced, such as by interface 15, to the relay client 14. Interface 15 is an ATM or IP signaling
30 interface that relays radio access network signaling, possibly H.323, SIP, IS-634, or others, to the Services Client 20. Additionally, a SS7 gateway 28 couples the core

network 10 to the SS7 network 18, a packet gateway 30 couples the core network 10 to the Internet 16 and a PSTN gateway 32 couples the core network 10 to the PSTN 14. The convention used in FIG. 1 and throughout the drawings is that arrowed lines denote signaling information while non-arrowed lines denote bearer information.

The CALEA feature server 26 provides the CALEA feature application within the core network 10. The CALEA feature server 26 interfaces to the services client 20 via a hypertext transfer protocol (HTTP) or other text based applications programming interface (HTTP/text API) 34. The CALEA feature server 26 further interfaces with the relay client 24 via a feature application programming interface (FAPI) 36 to control duplication of bearer streams and processing of in-band signaling in the duplicated bearer streams. Additionally, the CALEA feature server 26 interfaces with the law enforcement agency (LEA) 25 via GENMAP link 27, for providing out-of-band call signaling information such as dialed digits, call-waiting invocation, call feature invocation, conferencing adds/drops/etc. GENMAP, as is known in the art, generally refers to an ANSI-41, GSM MAP or similar signaling protocol.

The services client 20 provides the call processing engine within the core network 10 for providing communication services to users of the core network 10. The services client 20 maintains the call model and state for subscribers in the radio access network 12.

In accordance with the preferred embodiments of the invention and upon invocation of CALEA services for a targeted subscriber(s), the services client 20 provides point-in-call (PIC) call signaling information to the CALEA feature server via the interface 34. This interface is a

text based API such as HTTP or a more advanced API for feature processing. Additionally, the services client 20 interfaces with the relay client using a Relay Client Control Protocol (RCCP) connection 29 (based on H.248 signaling or MGCP) to manage the original bearer streams 31 pertaining to a subscriber's service requests.

The relay client 24 provides management of bearer streams 31, i.e., encoded voice or data, for active calls and/or conferences in the core network 10. In accordance with the preferred embodiments of the invention, the relay client 24 provides a capability to generate duplicate bearer streams 38 for communication to a LEA upon request from the CALEA feature server 26. Such duplicate bearer streams may be a single combined stream (full-duplex for a two party call and possibly all members of a conference call), or the relay client 24 may duplicate and provide all or a sub-set of all of the bearer streams 31 to the LEA 25, as requested by the LEA 25. Additionally, and in accordance with the preferred embodiments of the invention, the relay client 24 may also provide call signaling information in-band with the duplicate bearer stream 38, may exclude such call signaling information from the duplicate bearer stream or may provide the call signaling information as a separate data stream.

In accordance with the preferred embodiment of the invention shown in FIG. 1, the CALEA function resides within the CALEA feature server 26, which provides surveillance services within the core network 10 as a subscribed service. The service is authorized and activated under the guidance of the requesting LEA. The CALEA feature server 26 controls the relay client 24 via the xGCP link 36 (xGCP refers to the family of protocols SGCP, MGCP, and in the future MEGACO/H.248) to cause the relay client 24 to provide the

duplicate bearer streams 38 to the LEA 25 via the packet gateway 30 and the packet data network 16 in a manner that is unobtrusive to the original streams. The CALEA feature server 26 also controls the relay client 24 via the xGCP link 36 to provide any required in-band signaling for the duplicate bearer streams 38. The CALEA feature server 26 is triggered from the services client 20 via link 34 at required PICs to provide the required out-of-band signaling information to the LEA 25 over the GENMAP link 27.

10 A basic surveillance services flow that may be applied with the preferred embodiment of the invention shown in FIG. 1 may start with CALEA service logic being downloaded to the services client 20 when a "targeted" subscriber registers with the core network 10. This logic download provides the
15 services client 20 with access to the CALEA feature server 26 for the targeted subscriber.

The CALEA service logic may include the necessary triggers, and will include at least one trigger, and provides the LEA 25 with required call signaling information
20 (dialed digits, service invocation, etc.) and proper instructions for generating the duplicate bearer streams 38. Upon detection of the at least one trigger associated with the targeted subscriber, such as registration, call origination, call termination, service invocation (e.g.,
25 call waiting, conference call, call forwarding, message retrieval, etc.) the services client 20 call model implements the surveillance service logic, which, in turn, interfaces with the CALEA feature server 26. The CALEA feature server 26, in turn, interfaces with the relay client
30 24 to provide the duplicate bearer streams 38 (e.g., merged, individual or sub-set bearer streams) to the LEA 25 using RTP over a secure Internet connection (such as defined in

IPSec of the Internet Engineering Task Force) through the packet gateway 30. The CALEA feature server 26 forwards the requested signaling streams to the LEA 25 using the GENMAP link 27 over the IPSec through the packet gateway 30.

5 Importantly, the original call signaling and bearer streams 31 are unaffected. The relay client 24 becomes the anchor point for targeted subscribers engaged in active calls. Also, core path optimization is deactivated if the call hands-off to another core network.

10 A representative call flow 200 for the system shown in FIG. 1, is illustrated in FIG. 2, wherein like reference numerals are used to represent like processes. FIG. 2 represents a surveillance service wherein the bearer streams are duplicated for forwarding to the LEA 25. Not shown, is
15 an initial request by the LEA 25, via the packet gateway 30 for surveillance services in connection with a particular subscriber. This request contains the surveillance type information, which may be retained within the CALEA feature server 26, or as described in connection with alternate
20 preferred embodiments of the invention, in other suitable locations within the core network 10.

As shown in FIG. 2, the targeted subscriber originates a call and the call is about to be connected. The services client 20 forwards a call connect trigger 202 to the CALEA
25 feature server 26. The call connect trigger 202 includes information necessary for implementing the requested surveillance service, and may include the RTP stream endpoint(s), vocoder type, requesting LEA identification, requesting LEA address, and the like. The CALEA feature
30 server 26 forwards a duplicate bearer stream signal 204 using the xGCP link 26 to the relay client 24, and the relay

client 24 forwards the LEA address information 206 to the packet gateway 30.

The packet gateway 30 makes an IPSec negotiation request 208 to the requesting LEA 25 via an unsecured link 5 41. The security association is negotiated according to IPSec rules, and the LEA 25 provides an IPSec negotiation response 210. The packet gateway 30 sends an acknowledgement 212 of the IPSec negotiation to the relay client 24, and the relay client 24 begins sending the 10 duplicate bearer streams 38, using RTP. The duplicate bearer streams are then communicated from the packet gateway 30 to the LEA 25 using the negotiated secure connection.

One of ordinary skill in the art will appreciate the modifications necessary to the above-described call flow 200 15 for triggering surveillance services responsive to call termination, services invocation, and other similar events occurring within the communication network 700.

FIG. 3 shows a communication network 300 in accordance with an alternate preferred embodiment of the invention. 20 The communication network 300 includes a packet-based core network 310, and takes advantage of the distributed nature of the core network 310 for providing surveillance services. In accordance with the preferred embodiments of the invention, the communication network 300 makes use of 25 several functional elements that are typical of and therefore expected to be resident within the core network 310 for providing communication services. Advantageously, the architecture of communication network 300 minimizes additional development that would otherwise be required to 30 provide functions necessary to support surveillance services within the communication network 300.

The core network 310 includes a packet data gateway 312 for linking to a packet data network 314, an SS7 gateway 316 for linking to a PSTN 318, a circuit gateway 320, additional feature servers 322, a conference feature server 324, a
5 H.323/A+ Client Gatekeeper 326, and an access server 328. Subscribers (not shown) access the core network 310 via an access network 330, such as a radio access network, and the access server 328. The core network 310 further includes a subscriber services database 332, e.g., a home location
10 register database as is well known in cellular communication systems. As shown in FIG. 3, additional feature servers 322 may include a billing server 336, a location server 338 and a short message server 340.

As shown in FIG. 3, core network 310 also includes a
15 surveillance distribution server (SDS) 334. As will be described in more detail below, the SDS 334 may provide the following functions: conversion of call set-up messages and call-related information to a standard message format, for example, to the J-STD-025 message standard, for
20 communication to a requesting LEA; delivery of the standard messages to the LEA; initiation of requests to the core network elements to provide subscriber information, for example, location information; reception of packet data from other core network elements for communication to the LEA,
25 and support a subscriber surveillance database.

To support the functionality of the SDS 334, it may be necessary to interface the SDS 334 with the H.323/A+ Client gatekeeper 326 and one or more of the feature servers 322, such as location server 338. The implementation shown in
30 FIG. 3 does utilize and rely upon the conference feature server 324 being within or interfaced to the core network 310 to handle combining data from the surveillance subject

and associate for delivery to the LEA. A conference feature server 324 will typically exist within the core network 310 for supporting POTS features, such as three-way calling, call forwarding, etc.; however, it will also be appreciated 5 that the function of the conference feature server 324 may be provided within one of the additional feature servers 322, another element of the core network 310 or may be extracted from the core network 310.

It will also be appreciated that there may be several 10 locations within the core network 310 within which subscriber surveillance data may be retained. However, adaptation of the home location register (HLR) to include a data structure for retaining the subscriber surveillance data advantageously reduces the amount of provisioning 15 required for implementing surveillance services and provides an implementation cost savings. For purposes of the implementation shown in FIG. 3, it will be assumed that the HLR is utilized in this manner and accessed via the subscriber services management system 333 that is used for 20 provisioning. The surveillance data that may be included in the subscriber services database 332 is wire tap type, start date and time, stop date and time, IP addresses for the requesting LEAs, case identifications, and LEA identification information.

25 In accordance with the embodiment of the invention shown in FIG. 3, responsive to invocation of surveillance services, the SDS 334 instructs the access server 328 to generate duplicate bearer data packets and to transmit the duplicate bearer data packets to the conference feature 30 server 324. The conference feature server 324 combines and sums the duplicate bearer data packets into a single path and communicates them to the circuit gateway 320 to transmit

to the requesting LEA (not depicted). The circuit gateway communicates to the SDS 334 the circuit or circuits being used to transmit the bearer data to the LEA, and the SDS 334 also provides this information to the LEA.

5 The H.323 Client gatekeeper 326 detects when a call set-up message is being transmitted by a targeted subscriber within the access network 330. The H.323 Client gatekeeper 326 transmits duplicate call set-up messages to the SDS 334, and the SDS 334 translates these messages into standard
10 messages for communication to the LEA. The H.323 Client gatekeeper 326 will also transmit messages to the SDS 334 from other elements of the core network 310. For example, messages relating to the utilization of the feature servers 322 may be transmitted, or the subscriber services database
15 332 may transmit messages that the targeted subscriber has made changes to their feature profile. Additionally, the subscriber services database 332 will also inform the SDS 334 whenever the targeted subscriber has roamed into a different network.

20 By providing an interface to the billing server, the SDS 334 may obtain and retain billing records whenever surveillance services are provided to a LEA. Thus, the communication network operator may more accurately recoup the cost of providing surveillance services.

25 Surveillance services relating to short message data may be handled by either of the access server 328 or the H.323 Client gatekeeper 326 eliminating the need to interface the short message server 340 to the SDS 334. Whether the access server 328 or the H.323 Client gatekeeper
30 326 controls the transmission of short message data and information may depend on whether the short message data and information is considered bearer data or signaling data.

FIG. 4 illustrates a typical call flow 400 wherein surveillance services are provided using a network configured as shown in FIG. 3. At step 402, the targeted subscriber originates a communication, for example, by

5 dialing digits and pressing send on a cellular radiotelephone. At step 404, the H.323 Client gatekeeper 326 makes an inquiry of the subscriber services database 332, and at step 406 the surveillance services data is obtained from the subscriber services database and

10 communicated to the H.323 Client gatekeeper 326. From the H.323 Client gatekeeper 326, at step 408, the surveillance services data is communicated to the access server 328. Alternatively, the access server 328 may maintain a separate, local surveillance services database.

15 At step 410, the H.323 Client gatekeeper 326 continues with the targeted subscriber's origination request, and transmits a copy of the origination data to the SDS 334. The SDS 334 receives the origination data and translates the data to the standard data format and transmits the

20 translated origination data to the requesting LEA through the packet gateway 312, step 412. Once the origination attempt is answered at the far end, and bearer data, either voice or data, is sent between the targeted subscriber and the access server 328, at step 414, the access server 328

25 duplicates the bearer data and sends it to the conference feature server 324. The access server 328 must send duplicated bearer data for each LEA requesting surveillance services for the subject. That is, multiple LEAs may be requesting surveillance services on the same targeted

30 subscriber, and therefore multiple duplicate copies of the bearer data will be generated, one each for each requesting LEA.

The conference feature server 324 assigns resources to combine and transmit the duplicated bearer data to each of the requesting LEAs, and the combined data is then sent to the circuit gateway for transmission to the LEAs, step 5 416. At step 418, the circuit gateway transmits the combined data to the LEAs, and at step 420 the circuit gateway transmits circuit identification data to the SDS 334 for reporting to the LEAs in standard messages, step 422.

The SDS 334 may also request location data from the 10 location server 338. The location data is likewise placed into the standard message format by the SDS 334 and transmitted to the LEAs. Likewise, one of ordinary skill in the art will readily appreciate and understand the modifications necessary to the above-described call flow for 15 providing surveillance services triggered from call termination, services invocation, and other similar events occurring within the communication network 300.

FIG. 5 illustrates a communication network 500 similar in configuration to that shown in FIG. 1, and like elements 20 are identified using a reference numeral beginning with the number "5." For example, core network 10, in FIG. 1, is shown as core network 510 in FIG. 5. In FIG. 5, the CALEA feature server 526 is no longer resident within the core network 510, but instead is disposed external to the core 25 network 510. In this arrangement it is necessary to interface the CALEA feature server 526 to the services client 520, the relay client 524 and the packet gateway 530. Additionally, as shown in FIG. 5, the CALEA feature server 526 communicates via a link 542 with an authentication 30 authority 540, for example, a designated governmental authority, which can authenticate requests for surveillance services.

In a preferred embodiment of the invention, and in connection with the communication network 500, a LEA 525 requests surveillance services for a targeted subscriber over an IPSec secure connection via the packet gateway 530.

5 The services request is communicated through the core network 510 to the CALEA feature server 526. The CALEA feature server 526 engages in a dialogue with the authentication authority 540, and is provided all necessary information associated with the requested surveillance. The

10 CALEA feature server 526 communicates with the appropriate network operator, for example, the operator of core network 510, authorizing the surveillance request and placing the surveillance order.

The CALEA feature server 526 may then inject logic into

15 the appropriate network elements within core network 510, for example relay client 524, services client 520 and/or other feature servers and gateways, to enable the requested surveillance services.

When the targeted subscriber initiates a service that

20 triggers surveillance, for example, originating a call, the relay client 524 notifies the CALEA feature server 526, and the network elements within the core network 510 provide the CALEA feature server 526 with the necessary surveillance data, for example, location. The relay client 524 also

25 advises the assigned resource ID to be used for subscriber initiated service.

The CALEA feature server 526 instructs the relay client 524 to provide a duplicate bearer stream to the authorized LEA 525, using the LEA's IP address information provided

30 when the LEA 525 made the surveillance services request. Alternatively, the CALEA feature server 526 could request the multicast address currently being used for the target

subscriber and instruct the packet gateway 530 to send multicast information to the LEA's IP address. The relay client 524 routes the duplicate bearer stream to the LEA via the packet gateway 530 (and/or a circuit gateway). Other 5 feature servers within the core network 510 are also instructed to route call signaling, short message data, and the like to the LEA 525 via the packet gateway 530 and using the LEA's IP address.

As is appreciated from the embodiment of the invention 10 describe in connection with FIG. 5, surveillance services may be provided as an extracted feature. Thus, surveillance services may be added without extensive reconfiguration of the architecture of the core network 510. Providing authentication via the authentication authority 540 ensures 15 that surveillance services are not implemented absent appropriate authorization. Moreover, in accordance with the embodiment of the invention shown in FIG. 5, surveillance services may be implemented using existing customer equipment.

20 FIG. 6 illustrates a communication system 600 in accordance with another preferred embodiment of the invention. As in the previously described embodiments of the invention, signaling information is indicated by arrowed lines while bearer traffic is indicated by solid lines. The 25 system 600 includes a bearer distribution network 602 that is coupled to a packet data network 604 and to a PSTN 606. The communication system 600 also includes a radio access network 608 and a core network 610.

The bearer distribution network 602 functions to 30 transport IP bearer traffic (e.g. voice or data) within the communication network 600. For example, the bearer distribution network may include SDUs, MCUs, IP switches and

signaling and media gateways. It should be appreciated that various combinations of these elements may be used depending on the type of source and destination parties/devices and the services provided. For example, in communication systems supporting mobile-to-mobile calling and/or packet data calling services, network resources may not be required.

The radio access network 608 is coupled to both the bearer distribution network 602 and to the core network 610 and provides wide-area wireless communication services in accordance with one or more communication standards. More particularly, within the core network 610, the radio access network is coupled to a call control server 612. The control server 612 is a functional entity within the core network 610 that incorporates the IP network call/session establishment and feature interaction. This is a distillation of such functions as radio network controller, services client, session manager, and the like. The call control server 612 is also coupled to a CALEA feature server 614 within the core network 610.

A mobility server 616, a location server 618, a profile server(s) 620, an operations server 622 and other feature servers 624 are provided within the core network 610 and are coupled to the CALEA feature server 614. The mobility server 616 is the functional equivalent of the Visitor Location Register (VLR) of current cellular communication systems. The location server 618 manages the locations gathering and provides the best possible coordinate location of mobile subscribers operating in the radio access network 608. The profile server 620 is a repository of mobile subscribers require for feature management and control. A home location register (HLR) is an example of a profile

server 620. The operations server 622 provides the functionality and operations necessary to provision the CALEA feature server 614 with information required for providing surveillance services. For example, the
5 operations server 622 will provide the CALEA feature server 614 with the identity of the surveillance target as well as the identity of the LEA requesting the surveillance services.

The bearer distribution network is also coupled to a
10 collection gateway 626. The collection gateway 626 is a media gateway, which has an interface to law enforcement. It may also include functionality to encrypt/decrypt intercept signaling and bearer data, and may also contain multicast group client capability for intercepting multicast
15 subject content. The collection gateway 626 interfaces to an intercept access point 628, which is the collection point for surveillance content and data, and the point from which the LEAs access and acquire the surveillance content and data.

20 With reference still to FIG. 6, and reference also to FIGs. 7-10, the operation of the communication system 600 for providing surveillance services is described.

Upon reception of appropriate authorization from a law enforcement agency, for example, a court order authorizing
25 wiretapping, the operator provisions surveillance of the subject via the operations system. At step 702, the operations server 622 sends the provisioning information to the CALEA Feature Server 614. This includes the CASE ID which identifies the law enforcement agency and the
30 particular surveillance case. Also included is the subject's identity such as his or her directory number and name. If encryption of the signaling is desired, a key may

be distributed to the network entities that will provide surveillance information.

Based on the subscriber and agency information, the CALEA feature server 614 instructs the multicast client
5 function in the appropriate collection gateways 626 to listen for multicast announcements of the identified subject, step 704. This method permits early detection of potential resource shortages in the collection gateway 626. An alternative to this step 704 is for the CALEA feature
10 server 614 to directly assign collection gateway resources when a subject call is answered. Resources may include circuits and multicast bearer and signaling streams.

The CALEA feature server 614 instructs the Call Control Server 612 to add the specified subject to its surveillance
15 list. Any signaling related to the subject will be replicated and sent to the CALEA feature server 614, step 706. An alternative approach to this step 706 is to assign a multicast group (address) for all intercept signaling. The CALEA feature server 614 would be a receiving member of this
20 group. The CALEA feature server 614 also adds the subject to the surveillance list in other servers such as the profile server 620, the mobility server 616, the location server 618, and other feature servers 624.

At step 708, the subject, wireless subject 630,
25 originates a call to a party, participant-C 632, on the circuit switched public network (P-C). The radio access network 608 sends the origination to the call control server 612 for proper further processing, step 710. The call control server 612 recognizes that the origination is a
30 member of the surveillance subjects list and replicates the message to the CALEA feature server 614, step 712. The CALEA feature server 614 collects the call id, source and

destination party ids and the cell location required for signaling to the intercept access point 628. The cell id may be used to collect coordinate location information from the location server 618.

- 5 At step 714, the call control server 612 forwards the origination to the bearer distribution network 602 with access to the PSTN 606. The bearer distribution network 602 signals an origination (e.g. IAM) to the participant-C 632 across the public switched telephone network 606, step 716.
- 10 The terminating party, participant-C answers, step 718, and the answer is forwarded to the call control server 612, step 720.

- Noting the call is for a surveillance subject, the call control server 612 assigns multicast addresses for the
- 15 bearer stream terminations between the radio access network 608 and the bearer distribution network 602. A circuit termination is associated with the streams for delivery of information to/from the participant-C 632.

- The call control server 612 informs the CALEA feature
- 20 server 614 of the answer so that that interception by the collection gateway 626/intercept access point 628 may be enabled, step 724. The CALEA feature server 614 performs a proxy announcement (e.g., Service Access Point (SAP)) of the multicast sessions established for the subject
- 25 communications, step 726. The multicast client in the collection gateway 626 recognizes the announcement is for a session it was earlier instructed, by the CALEA feature server 614, to listen for. It enables reception of the subject's IP datagrams from the radio access network 608,
- 30 step 728. The multicast client enables reception of the subject's IP datagrams from the bearer distribution network 602, step 730.

The CALEA feature server 614 signals a call content pen instruction to the collection gateway 626, step 732. The subject identity, timestamp, call id, and other required parameters are provided. The collection gateway 626
5 forwards the open to the intercept access point 628, step 734.

The CALEA feature server 614 requests detailed location information of the subject from the location server 618, step 736. The location server 618 requests updated location
10 information from the radio access network 608, step 738. The radio access network 608 returns the current subject location, step 740. The location server 618 formats and forwards the response to the CALEA feature server 614, step 742.

15 The CALEA feature server 614 includes the collected location coordinates in an Answer sent to the collection gateway 626. Also included is the CASE ID and all collected information from the call set up signaling, step 744. The collection gateway 626 forwards this to the intercept access
20 point 628, step 746. At this point the collection gateway 626 captures the call content to and from the wireless subject 630 and sends it to the intercept access point 628. Any subject related signaling in the network is forwarded to the CALEA feature server 614, which sends the appropriate
25 signal to the intercept access point 628 as required, step 748.

It will be appreciated that in this embodiment of the invention does not require the signaling entities (e.g., control/feature servers) to replicate signaling since
30 designated intercept parties signaling may utilize one or more known multicast addresses/ports. Use of separate addresses enables wholesale special treatment such as

encryption, which might not be done on normal calls. Further still, calls such as mobile-to-mobile calls or PDG do not have to go through the relay client (e.g. relay client 24) or an MCU. It will be further appreciated that 5 the SDU could be incorporated into the radio access network, e.g., into the base transceiver stations of the CDMA cellular communication network.

This embodiment of the invention also enables the use of multicast and signaling related to joining multicast 10 groups. The join may be provided by a multicast client function adapted to the CALEA feature server, which joins the individual's multicast group when it is announced, e.g., via SAP. However, this may not be required since the CALEA feature server, e.g., CALEA feature server 614, can do an 15 MGCP Add of the subject's multicast bearer streams to the circuit (or packet) connection to the intercept access point 628.

FIG. 11 illustrates a communication network 1100 similar in configuration to that shown in FIG. 1, and like 20 elements are identified using a reference numeral beginning with the number "11." For example, core network 10, in FIG. 1, is shown as core network 1110 in FIG. 11. As shown in FIG. 11, the core network 1110 includes a services agent 1102 that interfaces with the services client 1120. In a 25 preferred embodiment of the invention, the services agent 1102 contains a menu of interception features, such as have been described herein, which can be applied to an intercept order from an authorized LEA. As will be described, the services agent 1102 permits regional variations of intercept 30 requirements to be applied to different targets within a single network using a common equipment design. For a given target and corresponding agency, specific bearer delivery

interfaces and event record formats can be selected, simultaneously, within a single network configuration. For example, a single target circuit switched call may be monitored by two LEAs, e.g., LEA 1125 and LEA 1140. For 5 example, LEA 1140 may require a circuit switched interface, e.g., interface 1141, for bearer traffic and a signaling interface, e.g., interface 1143, for signaling information such as TIA J-STD-025 event records. LEA 1125, however, may require a single packet data interface, e.g., interface 10 1141, for the delivery of both bearer traffic and signaling information such as ETSI EN 201 671 event records. Furthermore, home network based interception is required by many governments in addition to the visited network based interception called out by international standards.

15 In accordance with a preferred embodiment of the invention, the services agent 1102 includes a data structure associated with processing capability. Within the data structure, the services agent 1102 maintains a single target list that permits the services agent 1102 to administer both 20 home network based and visited network based surveillance target interception from a single location. The services agent 1102 may further contain a menu of surveillance features and associated logic, from which requesting agencies may select surveillance features to be associated 25 with a surveillance target upon requesting surveillance services.

The services agent 1102 administers initiation of surveillance services. The services agent 1102 associates a surveillance services requester, for example, a requesting 30 LEA 1125 or 1140, the services requested and a services client associated with the surveillance target, for example, services client 1120. The services agent 1102 locates

existing services clients upon receipt of a service request for the surveillance target, or provides the instantiation of a new services client for a surveillance target upon initial attachment of the surveillance target to the
5 network. Within the data structure, the services agent 1102 further maintains the list of intercept features and agency delivery addresses for each surveillance target.

In accordance with preferred embodiments of the invention, the services agent 1102 instructs the services
10 client 1120, or potentially passes appropriate logic to the services client 1120, to gather the appropriate surveillance features from the CALEA feature server 1126 for application against a specific surveillance target and for a specific LEA. Multiple features can be activated against the
15 surveillance target simultaneously. Since the services agent's function locates or creates services clients, there is minimal signaling impact to the system when the intercept target list is integrated into the services agent 1102.

As will be appreciated, this approach combines home and
20 network based interception into a single, unified approach as a home services client is established for a surveillance target even when the surveillance target has roamed into another network. The intercept feature loaded onto the CALEA feature server 1126 will determine the type of
25 interfaces, for example, interfaces 1141, 1142 and/or 1143, used for delivery, and the format of the information delivered. ETSI and TIA standards, as well as custom regional variations are defined as features on the CALEA feature server 1126, and assigned to each target on the
30 services agent 1102. The CALEA feature server 1126 communicates with the appropriate gateways via links 1127, 1145 and/or 1147. Various formats and interfaces for

specific agencies can be applied to a single or multiple surveillance target simultaneously.

The invention has been described in terms of several preferred embodiments, which are intended to be illustrative of the broad aspects of the invention. It will be understood that the invention is not limited in scope to the preferred embodiments described herein, but instead is limited only by the scope of the subjoined claims.

12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216